

3.Specification Tables



(3-1) Rated Output Table (STANDARD NET)

Model			2TNV70	3TNV70	3TNV76
Combustion type			IDI		
Aspiration			N/A	N/A	N/A
Number of cylinders — Bore × Stroke (mm × mm)			2 — 70 × 74	3 — 70 × 74	3 — 76 × 82
Displacement (cc)			570	854	1115
Revolution speed (min ⁻¹)			Output Net power kW (PS) [GROSS POWER kW]		
Industrial use	Rated Output	2000	6.0 (8.1) [6.2]	9.0 (12.2) [9.3]	11.8 (16.1) [12.3]
		2200	6.0 (9.0) [6.9]	9.9 (13.5) [10.3]	13.2 (17.9) [13.8]
		2400	7.3 (9.9) [7.7]	11.0 (14.9) [11.5]	14.3 (19.5) [15.1]
		2500	7.6 (10.3) [8.0]	11.4 (15.5) [12.0]	14.9 (20.3) [15.8]
		2600	7.9 (10.7) [8.3]	11.8 (16.1) [12.5]	15.5 (21.1) [16.5]
		2800	8.5 (11.6) [9.1]	12.8 (17.4) [14.1]	16.7 (22.7) [17.8]
		3000	9.1 (12.4) [9.8]	13.7 (18.6) [14.6]	17.9 (24.3) [19.2]
		3200	9.3 (12.7) [10.2]	14.0 (19.0) [15.1]	18.2 (24.8) [19.9]
		3400	9.6 (13.1) [10.7]	14.7 (20.0) [16.1]	19.3 (26.2) [21.2]
		3600	9.9 (13.5) [11.4]	15.4 (21.0) [17.0]	19.5 (26.5) [22.3]
Generator use	Rated Output	1500	—	6.7 (9.1) [6.8]	9.0 (12.2) [9.2]
		1800	—	8.0 (10.9) [8.2]	10.7 (14.6) [11.0]
		3000	8.5 (11.5)	13.3 (18.1) [14.3]	16.5 (22.5) [17.9]
		3600	10.0 (13.6)	16.0 (21.7) [17.6]	19.5 (26.5) [21.7]
	Cont. Rating	1500	—	6.1 (8.3) [6.2]	8.2 (11.1) [8.4]
		1800	—	7.3 (9.9) [7.5]	9.8 (13.3) [10.1]
		3000	7.7 (10.5)	12.1 (16.5) [13.1]	15.1 (20.5) [16.5]
		3600	9.1 (12.4)	14.5 (19.7) [16.1]	17.7 (24.1) [19.9]