

3.Specification Tables



(3-1) Rated Output Table (STANDARD NET)

Model			3TNM68		3TNM72	
Combustion type			IDI			
Aspiration			N/A		N/A	
Number of cylinders — Bore × Stroke (mm × mm)			3 — 68 × 72		3 — 72 × 74	
Displacement (cc)			784		904	
Revolution speed (min ⁻¹)			Output Net power kW (PS)			
Industrial use	Rated Output	2000	8.2	(11.1)	9.5	(12.9)
		2200	9.1	(12.3)	10.6	(14.4)
		2400	10.0	(13.6)	11.7	(15.9)
		2600	10.8	(14.7)	12.6	(17.1)
		2800	11.7	(15.9)	13.6	(18.5)
		3000	12.6	(17.1)	14.7	(20.0)
		3200	12.8	(17.4)	15.6	(21.2)
		3400	13.5	(18.3)	16.5	(22.4)
		3600	14.1	(19.2)	17.0	(23.1)
Generator use	Rated Output	1500	6.1	(8.3)	7.3	(9.9)
		1800	7.3	(10.0)	8.6	(11.7)
		3000	12.2	(16.6)	14.5	(19.7)
		3600	14.6	(19.9)	17.0	(23.1)
	Cont. Rating	1500	5.5	(7.5)	6.6	(9.0)
		1800	6.6	(9.0)	7.8	(10.6)
		3000	11.1	(15.1)	13.2	(17.9)
		3600	13.3	(18.0)	15.9	(21.6)